

AVAIL 2

FOR QUICK SPINS OR A FIRST CENTURY RIDE, AVAIL IS THE PERFECT ROAD COMPANION. SPEED, CONTROL, CONFIDENCE—GO WITH ALL THREE.



SPECIFICATIONS

FRAME	
SIZES	XS, S, M, L
COLORS	Charcoal
FRAME	ALUXX SL-grade aluminum
FORK	Composite, Alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect, 31.8mm
STEM	Giant Sport
SEATPOST	Giant D-Fuse, Composite
SADDLE	Liv Connect, Forward
PEDALS	Caged w/ toe clip and strap
DRIVETRAIN	
SHIFTERS	Shimano Tiagra
FRONT DERAILLEUR	Shimano Tiagra
REAR DERAILLEUR	Shimano Tiagra
BRAKES	Tektro R312
BRAKE LEVERS	Shimano Tiagra w/ Tektro RL721 sub lever
CASSETTE	Shimano Tiagra 12x30, 10-speed
CHAIN	KMC X10
CRANKSET	Shimano Tiagra, 34/50
BOTTOM BRACKET	Shimano, Press Fit
WHEELS	
RIMS	Giant S-R2
HUBS	Giant Tracker Sport Road, 26h
SPOKES	Stainless Steel, 14g
TIRES	Giant S-R4, Front and rear specific, 700x25

FRAME DESIGN

With a lightweight ALUXX SL aluminum frame that's built specifically for women riders, the all-new Avail is a versatile performer for all types of road adventures. From short training rides to long days in the saddle, its comfortable endurance positioning and easy handling keep you in control. The new D-Fuse seatpost quiets road vibration and reduces fatigue. Other features include an OverDrive steerer tube for precision steering and a PowerCore oversized bottom bracket for maximum pedaling efficiency.



FEATURES

- ALUXX SL-grade aluminum frame with compliant D-Fuse composite seatpost
- Composite fork with alloy OverDrive steerer absorbs
- Giant S-R2 rims, Giant Tracker Sport hubs, stainless spokes
- Shimano Tiagra 10-speed shifting
- Tektro rim brakes

U.S. Average Retail Price: \$1,105

GEOMETRY

Size	Part number	Head Angle	Seat Angle	Top Tube	Reach	Head Tube	Stack	Chain Stay	Wheel Base	Standover Height
Centim..		Degree	Degree	Centim..	Centim..	Centim..	Centim..	Centim..	Centim..	Inches
XS/43.0	N/A	70.5	75.0	51.5	36.6	13.5	53.0	42.0	99.8	26.6
S/46.5	N/A	72.0	74.5	52.5	37.2	15.0	55.0	42.0	99.0	27.6
M/50.0	N/A	72.0	74.0	54.0	37.7	17.0	56.7	42.0	100.0	28.7
L/53.5	N/A	72.0	74.0	55.5	38.6	19.0	58.8	42.0	101.6	30.1